

ThermoCraft™

Bringing Wood Science to Wood People

KNOTTY SOFTWOOD

Nordic Spruce.

ThermoCraft™ Nordic Spruce

Knotty	8 to 18 ft	HJT-Holz	Finland
SMALL TIGHT KNOTS	LENGTHS	PRODUCER	ORIGIN

WHAT OUR TEAM KNOWS

We know where Nordic Spruce fits.

Nordic Spruce is light in colour with a fine grain, and small, tight pin knots across the face. Our team offers advice to you, your builders and your specifiers on grade, profiles, fasteners and coatings.

FOR YOUR BUSINESS

A knotty line for cladding, soffits and ceilings that you can stock and sell, with our team behind every question your customers ask.

HOW WE SUPPLY IT

Milled ThermoCraft boards and profiles, made to our grade specs, in lengths and packs set to your program.



NORDIC SPRUCE CLADDING

DISTRIBUTORS AND DEALERS

Stock ThermoCraft Nordic Spruce.

Ask our sales team what's available.

+1 (778) 646-2810 | info@thermocraft.com | www.thermocraft.com

ThermoCraft™

MADE BY HJT-HOLZ


SPECIFICATION

Nordic Spruce, in detail.

SPECIES AND SUPPLY

BOTANICAL NAME	*Picea abies*
ALSO SOLD AS	Norway Spruce
GRADE	Knotty, small tight knots
ORIGIN	Finland
PRODUCER	HJT-Holz
LENGTHS	8 to 18 ft, odd and even lengths; net length 3 in under the nominal length
USES	Exterior cladding and soffits; interior ceilings; boards for sauna builders

PROFILES / NOMINAL INCHES

	S4S	1 x 5, 1 x 6, 1 x 8
	Fineline T&G	1 x 5, 1 x 6, 1 x 8
	V-Joint	1 x 5, 1 x 6, 1 x 8
	Bevel	1 x 6, 1 x 8 thick butt

Sections are schematic. Confirm net sizes and stock with our team.

Custom profiles on request. Talk to our sales team.



NORDIC SPRUCE CLADDING, MCCALL, IDAHO

HOW TO SPECIFY

1. **Choose** the species and profile.
2. **Confirm** sizes and lengths with our team.
3. **Ask** for samples.
4. **Order** through your stocking dealer or us.

INSTALLATION AND CARE

- Use stainless steel fasteners: the wood is slightly acidic.
- Leave a ventilated, drained cavity behind exterior cladding.
- Seal cut ends when the boards are pre-finished, to hold the colour.
- Left unfinished, it weathers to silver grey; moisture drives the change.

COATINGS

ThermoCraft takes paints, oils (not linseed) and waxes. Follow the coating maker's guidance.

+1 (778) 646-2810 | **info@thermocraft.com** | **www.thermocraft.com**